

# Cable Management

## MLTC and MLTFC Series

### Pan-Steel® Coated Steel Cable Ties

#### Features and Benefits

Ideal for applications where extra protection is required from edges and dissimilar metal applications. With the advantages of the MLT range on the previous page

#### Features & Benefits

- **MLTC:** Nylon 11 selective coating provides additional edge protection and prevents corrosion between dissimilar metals.
- **MLTFC:** Polyester overall coating, available in various colours for identification purposes, please contact us for information.
- Self-locking head design speeds installation and locks into place at any length along the tie body.
- AISI 316 Stainless steel.
- UV resistant, low smoke, halogen-free material.
- Temperature tolerance -40°C to + 140°C



#### Approvals

- UL Listing E56854
- CE EN50146
- Det Norske Veritas Cert. # E-6540, E-6539
- SAE AS 23190 (formerly MS23109E)

Order Description	Length	Width	Thick <sup>#</sup>	Max. Bundle Dia.	Min. Bundle Dia.	Min. Tensile Strength	Recommended Installation Tool
<b>MLTC - Heavy Cross Section Selectively Coated Ties - AISI 316 Stainless Steel</b>							
MLTC2H-LP316	201	7.9	0.25	51	12.7	1112	GS4MT, HTMT, PPTMT, ST2MT, PBMT
MLTC4H-LP316	362	7.9	0.25	102	12.7		
MLTC6H-LP316	521	7.9	0.25	152	12.7		
MLTC8H-LP316	679	7.9	0.25	203	12.7		
MLTC10H-LP316	838	7.9	0.25	254	12.7		
<b>MLTFC* - Heavy Cross Section Coated Ties - AISI 316 Stainless Steel</b>							
MLTFC2H-LP316RD	201	7.9	0.25	51	12.7	1112	GS4MT, HTMT, PPTMT, ST2MT, PBMT
MLTFC4H-LP316RD	362	7.9	0.25	102	12.7		
MLTFC6H-LP316RD	521	7.9	0.25	152	12.7		
MLTFC2H-LP316YL	201	7.9	0.25	51	12.7		
MLTFC4H-LP316YL	362	7.9	0.25	102	12.7		
MLTFC6H-LP316YL	521	7.9	0.25	152	12.7		
MLTFC2H-LP316GR	201	7.9	0.25	51	12.7		
MLTFC4H-LP316GR	362	7.9	0.25	102	12.7		
MLTFC6H-LP316GR	521	7.9	0.25	152	12.7		
MLTFC2H-LP316BU	201	7.9	0.25	51	12.7		
MLTFC4H-LP316BU	362	7.9	0.25	102	12.7		
MLTFC6H-LP316BU	521	7.9	0.25	152	12.7		

\*MLTFC: Above table only shows colours Red (RD), Yellow (YL), Green (GN), and Blue (BU). Also available are Black(-) and White (WH).

<sup>#</sup> Base material less coating

Dimension in millimeters unless otherwise stated.