





#### **Product Dimensions Selection Table**

Dimensions as	Dimensions After Recovery											
Dimension	н	J	н	J	<b>P</b> ±10%	<b>R</b> ±10%	<b>S</b> ±10%	<b>T</b> ±20%	<b>U</b> ±20%	<b>JO</b> ±20%	<b>HW</b> ±20%	<b>JW</b> ±20%
Material	2	25										
Part Number												
204W511-25	24	16	9.2	2.8	38	21	3.0	1.0	-	10	1.6	0.9
224W511-25	24	16	9.2	2.8	25	25	19	3.0	1.0	10	1.6	0.9

As supplied dimensions may be slightly reduced due to the nature of the material. After recovery sizes are not affected. All dimensions in millimetres unless otherwise stated.

Offering extra high shrink ratio for the latest miniature ultra lightweight wires and micro connectors.

### **Ordering Information**

- Standard colour Black.
- Size selection please refer to the table above.
- Specify the product name, material and coating required, as per example.

#### Part Number Example:

## 204W221-25-0

Straight moulded part in fluid resistant elastomer, colour black.

# toriolo Avoiloble

Materials Available		Environmental Adhesives Available				
Material	Material Description		Optional Pre-coat	Optional User Applied		
-25	Fluid resistant elastomer		/225	S-1017 or S-1048 or S-1125		

For more information on materials and adhesives, please refer to relevant sections of this catalogue.

© 2015 IS-Group all rights reserved no unauthorised reproduction