

Moulded Parts and Shapes

101A011 to 094

End Caps

Heat shrinkable

Provide optimum water-proofing and environmental protection for underwater, underground, or outdoor applications. Highly resistant to moisture, fungus and weathering. Used for protecting cable and pipes, or capping unused outlets in transitions, providing an environmental seal when used with adhesive.

Ordering Information

- Size selection please refer to table below.
- When ordering specify the product name, size, material, coating, as per Part Number System.
- Adhesive coating is optional. If added the entry dimensions will be reduced by 1.5mm.

Part Number Example:

101A031-25/86-0

Moulded part in fluid resistant polyolefin, with adhesive coating, colour black.

As supplied



After Recovery



Product Dimensions Selection Table

Dimensions as Supplied		Dimensions After Recovery		
Dimension	H	H	P Nom.	HW ±20%
Part Number				
101A011	5.1	2.00	22.90	1.02
101A021	7.40	3.30	25.40	1.27
101A031	10.20	4.80	30.50	1.52
101A041	15.20	6.40	40.60	1.78
101A062	25.40	11.40	68.80	2.29
101A083	50.80	22.90	101.60	2.79
101A094	83.80	38.10	114.30	3.05

All dimensions in mm unless otherwise stated

Materials Available

Material	Material Description
-3	Semi-rigid polyolefin
-4	Flexible polyolefin
-12	Fluoro-elastomer
-25	Fluid resistant elastomer
-100	Polyolefin, Zerohal

Environmental Adhesives Available

Optional Pre-coat	Optional User Applied
/42 or /86	S-1017 or S-1048
/42 or /86	S-1017 or S-1048
N/A	S-1255-04
/42 or /86 or /225	S-1017 or S-1048 or S-1125
/86 or /180	S-1048 or S-1030

For more information on materials and adhesives, please refer to relevant sections of this catalogue.

SSC-1 to 7 End Caps Heat shrinkable

As supplied



After Recovery



These SSC heat shrinkable end caps are made from a thermally stabilised modified polyolefin, which makes them highly resistant to moisture, fungus and weathering

- Electrical insulation to 1000 V
- Temperature rating -40°C to 85°C
- Minimum shrink temperature 121°C

Ordering Information

- Standard colour Black.
- Size selection please refer to table below.
- Packaged individually

Other styles and derivatives are available to special order, please contact for details.

Product Dimensions Selection Table

Dimensions as Supplied		Dimensions After Recovery		
Dimension	H	H	P Nom.	HW ±20%
Part Number				
SSC-1-xx	10.00	4.00	33.50	2.00
SSC-2-xx	20.00	7.50	55.30	2.30
SSC-3-xx	35.00	15.00	89.90	3.00
SSC-4-xx	55.00	25.00	143.20	3.30
SSC-5-xx	75.00	32.00	150.10	3.30
SSC-6-xx	100.00	45.00	162.50	4.00
SSC-7-xx	120.00	70.00	145.00	3.80

All dimensions in mm unless otherwise stated

xx - Ordering Information

** Material	Material Description
XU	Sealing end cap, uncoated
X	Sealing end cap, with adhesive (standard)
XTV	Sealing end cap, with adhesive, plus c/w pressure valve