

TYPE I • NYLON Tape CID-A-A-52080 Braided Lacing Tape

Part Number		Size	Breaking Strength	Tape Width		Tape Thickness		Spool Sizes
Br	Gu	Mil-Spec	Kg (Min.)	mm (Min.)	mm (Max.)	mm (Min.)	mm (Max.)	Metres
101	26	1	61.23	4.57	5.59	0.33	0.48	228
102	23	2	36.29	2.51	3.07	0.30	0.46	228
103	18	3	22.68	1.96	2.39	0.28	0.43	457
104	22	4	11.34	1.37	1.68	0.23	0.38	457
105	20	5	6.80	1.14	1.40	0.15	0.36	457
n/a	21	n/a	9.07	1.42	1.73	0.13	0.28	457
n/a	15	n/a	3.18	0.74	0.89	0.03	0.23	457

Standard colours are Natural and Black, for additional colour choices please contact us.
Dimension in Metric unless otherwise stated

TYPE II • POLYESTER Tape CID-A-A-52081 Braided Lacing Tape

Part Number		Size	Breaking Strength	Tape Width		Tape Thickness		Spool Sizes
Br	Gu	Mil-Spec	Kg (Min.)	mm (Min.)	mm (Max.)	mm (Min.)	mm (Max.)	Metres
201	26D	1	61.23	4.57	5.59	0.33	0.48	228
202	23D	2	36.29	2.51	3.07	0.30	0.46	228
203	18D	3	22.68	1.96	2.39	0.28	0.43	457
204	22D	4	11.34	1.37	1.68	0.23	0.38	457
205	21D	5	6.80	1.14	1.40	0.15	0.36	457
n/a	20D	n/a	5.44	1.09	1.35	0.10	0.25	457
n/a	15D	n/a	1.81	0.74	0.89	0.05	0.20	457

Standard colours are Natural and Black, for additional colour choices please contact us.
Dimension in Metric unless otherwise stated

TYPE III • TEFLON Tape CID-A-A-52082 Braided Lacing Tape

Part Number		Size	Breaking Strength	Tape Width		Tape Thickness		Spool Sizes
Br	Gu	Mil-Spec	Kg (Min.)	mm (Min.)	mm (Max.)	mm (Min.)	mm (Max.)	Metres
302	256	2	13.61	2.74	3.35	0.23	0.36	228
304	231	4	6.80	1.5	1.83	0.23	0.36	457
305	n/a	5	4.50	0.58	0.71	0.23	0.36	457
n/a	230	n/a	6.35	0.71	0.86	0.64	0.79	457
n/a	302	n/a	1.81	0.25	-	-	-	457

Standard colours: Natural (Dark Brown) only, Teflon fibres cannot be dyed or coloured.
Finishes available: 'unfinished' and 'synthetic' only
Dimension in Metric unless otherwise stated

Glass, Nomex® and Nylon Braided Lacing Tape and Twisted Cord Selection Guide

TYPE IV • GLASS Tape CID-A-A-52083 Braided Lacing Tape

Part Number		Size	Breaking Strength	Tape Width		Tape Thickness		Spool Sizes
Br	Gu	Mil-Spec	Kg (Min.)	mm (Min.)	mm (Max.)	mm (Min.)	mm (Max.)	Metres
401	26X	1	90.72	5.16	6.30	0.33	0.48	228
402	23X	2	45.36	2.51	3.07	0.33	0.48	228
403	18X	3	34.02	1.96	2.39	0.33	0.48	457
404	22X	4	22.68	1.37	1.68	0.33	0.48	457
405	n/a	5	22.68	1.14	1.40	0.33	0.48	457
n/a	21X	n/a	31.75	1.73	2.11	0.30	0.46	457

Standard colours are Natural (White) and Black, fibreglass cannot be dyed but finish may be pigmented Black.
Dimension in Metric unless otherwise stated

TYPE V • NOMEX® Tape CID-A-A-52084 Braided Lacing Tape

Part Number		Size	Breaking Strength	Tape Width		Tape Thickness		Spool Sizes
Br	Gu	Mil-Spec	Kg (Min.)	mm (Min.)	mm (Max.)	mm (Min.)	mm (Max.)	Metres
501	726	1	38.56	4.57	5.59	0.33	0.48	228
502	723	2	22.68	2.51	3.07	0.28	0.43	228
503	718	3	15.88	1.73	2.11	0.23	0.38	457
504	722	4	11.34	1.27	1.55	0.18	0.33	457
n/a	1342	n/a	31.75	2.06	2.51	0.43	0.58	228
n/a	946	n/a	2.27	0.30	-	-	-	457

Standard colours are Natural (off White) with a Green tracer. Additional colour choices with or without tracer please contact us.
Dimension in Metric unless otherwise stated

TYPE P • NYLON Cord MIL-T-713 Twisted cord

Part Number		Size	Breaking Strength	Approximate Yield	Diameter		Spool Sizes
Br	Gu	Mil-Spec	Kg (Min.)	Metres per Kg	mm (Min.)	mm (Max.)	Kg
111-2	n/a	1	31.75	273 Wax Finish	0.91	1.12	0.45
111-1	n/a	1	31.75	350 No Finish	0.91	1.12	0.45
112-2	n/a	2	21.77	446 Wax Finish	0.53	0.74	0.45
112-1	n/a	2	21.77	595 No Finish	0.53	0.74	0.45
113-2	n/a	3	14.51	558 Wax Finish	0.48	0.69	0.45
113-1	n/a	3	14.51	744 No Finish	0.48	0.69	0.45

Standard colours are Natural (off White) or Black, no other colours available.
Dimension in Metric unless otherwise stated